



ZetaLube

A New Lubricity Dimension
Evolved From Experience



ZetaLube 224 Heat Transfer Oil

Description

Formulated with quality mineral oil and special additives, ZetaLube 224 is designed to provide maintenance professionals/engineers an economical and efficient circulating fluid for any heat transfer system.



MAGNA INDUSTRIAL CO. LIMITED
Total Quality Maintenance

www.magnagroup.com

Magna Industrial reserves the right to modify or change this product for purpose of improving its performance characteristics ©2009 Magna Industrial Co. Limited.

The ZetaLube trade mark is the property of ITW, Inc. and is used under licence by Magna Industrial Co. Limited





Features and Benefits

- Offers good fluidity so as to minimize the energy and costs required to pump and circulate the oils.
- Formidable thermal conductivity to optimize the efficiency and to minimize the costs of the heat transfer system.
- Excellent thermal stability – minimizes the fluctuation of temperatures and eliminates the formation of sludge and deposits in the heat transfer system.
- Low volatility helps eliminate vapor lock in circulating pumps and reduces the possibility of pump cavitations.
- Provides uniform rate of heat transfer - reduces the risk of overheating in any particular spot of the system.

Recommended Applications

- For enclosed heat transfer system in the production processes of :
 - Asphalt and coal tar
 - Chemicals and pharmaceuticals manufacturing
 - Fiberboards
 - Greases
 - Plywood laminating
 - Rubber and plastics
 - Sheet metal laminating
 - Soaps
 - Textiles
 - Varnish and resins manufacturers
 - And many more

Typical Data

TEST	ISO VG 32
Colour	Light Amber
Density, kg/L @ 20°C	0.864
Viscosity, cSt @ 40°C	32
Flash Point <Close Cup> °C	>210
Pour Point, °C	-9
Copper Strip Test	1a

The data shown is typical value and may vary.

Pack-size

205 Litre Metal Drum & 20 Litre Plastic Container

Authorized Distributor